

## X5 Centrifugal Air Curtain



The KC air curtain maintains environmental separation with a light flow of air, that not only results in lowered energy costs but also helps in preventing air borne contaminants & deterring flying insects from moving from one open space to another-enhancing sanitation & hygiene. Applications Entrance of Industries, Restaurants, Offices, Malls & other commercial places.

### Features

- Cooling Retention Effects: Air Curtains Prevents cold air to go outside & hot air to come inside.
- Super Sleek Design: Aesthetics that speaks of Slim design & looks apt for any modern environment.
- Resists Ingress of Dirt & Insects: The even air flow pressure helps in keeping away insects.
- Velocity Control Feature: Gives full access to control the mode of air curtain depending on door height.
- Optional remote control the product has two options of remote control or manual control, with 2 speeds copper motor

### Product Specification

Mounting Height: 2.5~3.5m

Model	Voltage	Power	Air Volume	Speed	Noise	N.W.	Dimensions
FM-3509S-L/Y (X5)	220V~50Hz	235W	1260m <sup>3</sup> /h	17m/s	50dB	12.5kg	900x200x230mm
FM-3510S-L/Y (X5)	220V~50Hz	250W	1300m <sup>3</sup> /h	17m/s	51dB	13.0kg	1000x200x230mm
FM-3512S-L/Y (X5)	220V~50Hz	290W	1700m <sup>3</sup> /h	17m/s	51dB	15.0kg	1200x200x230mm
FM-3515S-L/Y (X5)	220V~50Hz	380W	2100m <sup>3</sup> /h	17m/s	52dB	20kg	1500x200x230mm
FM-3518S-L/Y (X5)	220V~50Hz	435W	2500m <sup>3</sup> /h	17m/s	53dB	23.5kg	1800x200x230mm
FM-3520S-L/Y (X5)	220V~50Hz	450W	2800m <sup>3</sup> /h	17m/s	54dB	27.5kg	2000x200x230mm
FM-4009S-L/Y (X5)	220V~50Hz	300W	1520m <sup>3</sup> /h	21m/s	52dB	12.5kg	900x200x230mm
FM-4010S-L/Y (X5)	220V~50Hz	320W	1800m <sup>3</sup> /h	21m/s	53dB	13.0kg	1000x200x230mm
FM-4012S-L/Y (X5)	220V~50Hz	360W	2030m <sup>3</sup> /h	21m/s	54dB	15.0kg	1200x200x230mm
FM-4015S-L/Y (X5)	220V~50Hz	480W	2500m <sup>3</sup> /h	21m/s	55dB	20kg	1500x200x230mm
FM-4018S-L/Y (X5)	220V~50Hz	520W	3000m <sup>3</sup> /h	21m/s	58dB	23.5kg	1800x200x230mm
FM-4020S-L/Y (X5)	220V~50Hz	540W	3300m <sup>3</sup> /h	21m/s	60dB	27.5kg	2000x200x230mm